### SEE PAGE 2 FOR A LIST OF ACCESSORIES!



Model 140 shown with optional glass door.

### Design features:

DURASTALL® Model 140 & 142 includes...

- ß Slip-resistant floor with drain
- ß Brass shower valve and head
- ß Shower curtain and curtain rod
- ß Safety railing with molded-in soap dish and shampoo holder
- ß Mold and mildew-resistant components
- ß Knock-down construction makes portability extremely easy and is free-standing when assembled.
- ß Two styles of optional shower doors are available.
- ß Easy to assemble and install.


#### ß Available in both standard and extended bases;

Model 140 Standard Base



Standard bases include a PVC drain for direct connection to a 2" (Sch. 40) ABS, PVC or iron DWV pipe.

### Model 142 Extended Base



Extended bases eliminate the need to position the **shower stall base directly over the floor drain. This offset** allows for greater freedom in positioning the shower. Includes side outlet drain for 1-1/2" PVC pipe.

# **Specifications**

Model	Color	Size	Base	Α	В	C	D	UPC
140	White	36" X 36"	Standard	36-5/8"	75-3/8"	18-5/16"	28"	6 71031 00316 4
142	White	36" X 36"	Extended	36-5/8"	77-7/8"	18-5/16"	28"	6 71031 00317 1



General: Furnish and install as shown on plans, free-standing DURASTALL Shower Stall model \_\_\_\_\_(140, 142) as manufactured by E.L. Mustee & Sons, Inc. Consists of three, white, high-gloss thermoplastic walls, molded top frame, rigid aluminum front supports, slip-resistant 36" x 36" base, one-piece wrap-around railing with built-in soap dish and container. Skid-resistant floor with drain assembly, shower valve and head, shower curtain and rod, plus assembly hardware. Placement of valve assembly to be determined by installer.



E.L. Mustee & Sons, Inc. E-mail: info@mustee.com.

- 5431 West 164th Street
- Brook Park, OH 44142
- · Phone: 216.267.3100

Fax: 216.267.9997

Web: www.mustee.com
Proudly made in the USA



# 140 & 142 DURASTALL® Shower Doors



## **Design features:**

- Both doors fit all DURASTALL® shower stalls
- Sturdy, rust-resistant. engineered aluminum frame with polished chrome finish
- May be hung to open to accommodate a left or right hand opening
- Continuous-pull handle with magnetic seal
- Easy to install and clean...all components are mold and mildew resistant.
- Door height is 64"

### **Standard Door**

Model	Type Panel	UPC	Opening (W x H)	Height
45.700	Obscure Crystal Styrene	6 71031 00169 6	28" x 64"	64"

### **Glass Door**

Model	Type Panel	UPC	Opening (W x H)	Height
48.700	Obscure Glass	6 71031 00170 2	28" x 64"	64"

