

# 27F and 27W UTILATWIN® Laundry/Utility Tubs — Premier

#### SEE PAGE 2 FOR A LIST OF ACCESSORIES!



### **Design features:**

- High strength, one piece molded construction
- Produced with Mustee's proprietary structural thermoplastic resins and innovative cellular molding process creating extreme strength & durability
- Includes Twin-Drain Waste connector which joins drain assemblies to assure rapid and uniform waste water discharge...includes washers, slip nuts and stoppers.
- Divider wall between tubs is recessed one inch, permitting water to overflow from one tub to other, prevents water spilling onto floor.
- Large, self-draining back shelf with retainer curb that prohibits water runoff except into tub.
- 19 Gallon capacity per tub, extra deep 13" tubs with smooth surfaces
- Connects to standard 1½" P or S trap
- Accommodates single or dual-handle faucets. 4" or 8" centers
- Floor model includes heavy gauge steel legs with adjustable levelers
- Wall model includes wall mounting bracket, side supports and mounting hardware for securing tub to concrete or stud wall
- Mold and mildew-resistant components
- Easy to assemble and install
- Color-fast white finish

#### **Code Accepted:**

UTILATUB® and UTILATWIN® Laundry/Utility Tubs meet or exceed performance requirements as listed:


- International Association of Plumbing and Mechanical Officials (IAPMO)® Listed
- Warnock Hersey® (Canada) Listed—CSA test standards: Laundry Tray #B45.0 and #B45.5; Drain #B125
- American National Standards Institute (ANSI)—Specification Z 124.6






# **Specifications**

Colors & Models:	Model	Mounting	HxWxD	UPC
White	27F	Floor	34" x 40" x 24"	6 71031 00057 6
White	27W	Wall	34" x 40" x 24"	6 71031 00058 3






**General:** Furnish and install as shown on plans, UTILATWIN® Twin Laundry/Utility Tub model\_\_\_\_(27F, 27W), as manufactured by E.L. Mustee & Sons, Inc. Tub shall be one-piece molded construction using structural thermoplastics with matched metal molds under extreme heat and pressure. Tub to include integrally molded drains, twin drain waste coupling, recessed divider wall between tubs and twin drain assembly for connection to standard 1-1/2" P or S-trap, stoppers and wall mounting hardware or heavy gauge steel legs with built-in levelers. 19 gallon capacity per tub, each tub 13" deep. Shall meet ANSI Specification Z 124.6. Color: White. Weight: 27F 40 lbs.; 27W 40 lbs.



E.L. Mustee & Sons, Inc. • 5431 West 164th Street • Brook Park, OH 44142 • Phone: 216.267.3100 • Fax: 216.267.9997 E-mail: info@mustee.com. • Web: www.mustee.com • Proudly made in the USA



# 27F and 27W UTILATWIN® Laundry/Utility Tub Accessories



## Faucet



Model No.	UPC
93.600	6 71031 00232 7

Chrome finish, 4" center set brass faucet. 6" swing spout with aerator, level handles, replaceable seats and stems. Areator or hose end.

### Faucet Block



Model No.	UPC
20.600	6 71031 00031 6

Used when water supply lines are above the tub. Mounts to tub shelf when using a clamp-on faucet.

# HandiFlo™ Fitting



Model No.	UPC
94.700	6 71031 00287 7

Dispenses water from washing machine discharge hose into laundry tub. Eliminates draping washer machine hose over back/side wall of laundry tub and conceals discharge hose. Mounts to back or side wall of laundry tub, includes mounting hardware.

